




### Setsolar 750W solar panel



SETSOLAR manufactures its own photovoltaic modules using guaranteed and certified materials. This module meets industry standards for consumer safety and reliability and is covered by a comprehensive 20 year warranty. Low-iron tempered glass is designed to resist impact and increase light transmittance, thus improving daily power generation. Encapsulating the solar cells between Tempered Glass / EVA / Tedlar guarantees a durable protection for the cells during extreme weather conditions. The strong aluminium frame with pre-drilled mounting holes allow for easy installation. Each solar module is equipped with a special IP55 junction box and protective bypass diodes. Furthermore is each solar module submitted to an individual quality inspection, certifying product quality and output power performance. Modules designed and manufactured according to IEC 61215 & IEC 61730 standards. Modules designed and manufactured according to IEC 61215 & IEC 61730 standards..


#### APPLICATIONS

- Water pumping
- Signalling
- Billboard illumination
- Rural Electrification
- Telecommunication
- Streetlights


## SetsolarM750 - Data sheet

<b>TYPICAL PERFORMANCE CHARACTERISTICS</b>					
	65	70	75	80	85
Typical power (Wp)	65	70	75	80	85
Tolerance (%)	+- 5%				
Voltage at max.power (V)	17.0	17.3	17.6	17.9	18.2
Current at max.power (A)	3.90	4.10	4.30	4.50	4.70
Open circuit voltage (Voc)	21.4	21.6	21.8	22.0	22.2
Short circuit current (Isc)	4.50	4.70	4.90	5.10	5.30

<b>TEMPERATURE COEFFICIENTS</b>	
Voltage -	79.20mV / degree C
Current	+1.55mA / degree C
Power	-0.46% / degree C
NOCT (degrees)	45
<b>CELLS</b>	
Type	Monocrystalline
Dimensions	125mm x 125mm
Layout	36 cells (4rows x 9cells)
<b>GENERAL INFORMATION</b>	
Maximum System voltage	715V
Diodes	2 x 10A bypass
Weight (kg)	7.7
Frame	25mm black powder-coated aluminium
Packaging	4 modules per carton box
Type of connection	Junction box
<b>WARRANTY</b>	
Product	2 years
Power output Terrestrial:	20 years / 80% yield
Marine:	10 years / 90% yield



## SetsolarM750 - Data sheet



### CONTACT US

Sales and consulting:  
[geoff@planmypower.co.za](mailto:geoff@planmypower.co.za)

Services:  
[priscilla@planmypower.co.za](mailto:priscilla@planmypower.co.za)

Telephone  
+27 (0) 87 802 8479  
+27 (0) 11 678 5101  
+27 (0) 11 678 9184